




25W Fanless X-Band Block Up Converter

KEY FEATURES


- ◆ Output frequency 7.90 - 8.4 GHz
- ◆ L.O. 6.95 GHz
- ◆ Based on GaN technology which enables high efficiency, low power consumption and high reliability.
- ◆ Incomparable low power consumption (87W max)
- ◆ Auto-ranging powering 15 - 60 VDC
- ◆ High power efficiency (25W min over temperature)
- ◆ Digital temperature compensation
- ◆ Field-exchangeable (F/N) IF connector
- ◆ Optional M&C - combined RS-232/485 / Ethernet (HTTP and SNMP ver. 2 & 3) / FSK (optional)
- ◆ Internal 10MHz high stability reference (optional)
- ◆ Special Feature: Chinese GUI (optional)

ABE25X / ABE25XF



This smallest and lightest fanless 25W L-To X-Band Block Up Converter is based on GaN technology. It could be mounted directly on a feed horn. The unit can be powered either with 24VDC or 48VDC. Unit can use either external or internal 10MHz reference.

Mechanical Drawing





25W Fanless X-Band Block Up Converter

TECHNICAL SPECIFICATIONS

RF frequency		7.90 to 8.40 GHz
Local oscillator		6.95 GHz
IF frequency		950 to 1,450 MHz
Output power		25 W (+43.9 dBm min.)
IF connector		N-type or F-type (field-exchangeable)
Power supply : auto-ranging via IF connector		+15 ~ +60 VDC, 87W max.
Output interface		CPR-137G, CPR-112G, WR-90, WR-112G
Gain		68 dB min.
IMD3 (two tones)		-26 dBc max. 2 signal 5 MHz apart at P-LINEAR
L.O. leakage		-45 dBm max.
Spurious		-53 dBc max.
Spectral regrowth (QPSK at 1.5x and OQPSK at 1.0x symbol rate offset with 2dB back-off from rated output power)		-30 dBc
Requirement for external reference: frequency input power		via IF cable 10 MHz (sine-wave) -5 to +5 dBm @ input port
TX Gain variation		± 0.5 dB over 40 MHz ± 1.8 dB over full band
TX Gain stability over temperature range		± 1.5 dB typ., ± 1.8 dB max.
Phase noise (Exceeds Intelsat's standard IESS308/309)		-55 dBc/Hz max. @ 10 Hz
		-65 dBc/Hz max. @ 100 Hz
		-75 dBc/Hz max. @ 1 KHz
		-85 dBc/Hz max. @ 10 KHz
		-95 dBc/Hz max. @ 100 KHz
		-115 dBc/Hz max. @ 1 MHz
Noise power density	Transmit Receive	-66 dBm/Hz (max.) -157 dBm/Hz (max.)
M&C (optional)		RS-232/485 / Ethernet / FSK (optional)
Noise figure		15 dB max.
Input V.S.W.R.		1.5 : 1 max.
Output V.S.W.R.		1.5 : 1 max.
Mute		Shut off the HPA if L.O. unlocked
Status LED Amplifier L.O. 10MHz	RED GREEN GREEN GREEN GREEN blinking RED	Summary alarm All OK All OK L.O. is set to 6.95 GHz External 10MHz reference Internal 10MHz reference No 10MHz reference detected
Temperature range (ambient) operating storage		-40 deg C to +55 deg C -55 deg C to +85 deg C
Vibration and shock		Complies with MIL-STD-810E
IP rating		IP67
Dimensions & housing		195 (L) x 120 (W) x 87 (H) mm 7.67" (L) x 4.72" (W) x 3.42" (H)
Weight		2.76 kg (6.1 lbs) max.